

09/07/99
10490 U.S. PTO

A

Please type a plus sign (+) inside this box → ☒

PTO/SB/05 (4/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. RCA 88495
First Inventor or Application Identifier Parthasarathy, et al.
Title Code Mapping in a Trellis Decoder
Express Mail Label No. EL278371849US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 28]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 11]
4. Oath or Declaration [Total Pages 1]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submissions (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☒ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement (when there is an assignee) ☒ Power of Attorney
9. ☐ English Translation Document (if applicable)
10. ☒ Information Disclosure Statement (IDS)/PTO-1449 [7] Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ * Small Entity Statement(s) filed in prior application, Status still proper and desired (PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
15. ☐ Other:

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____

Prior application information: Examiner _____ Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label (Insert Customer No. or Attach bar code label here) or ☐ Correspondence address below

Name	Joseph S. Tripoli				
	Thomson Multimedia Licensing Inc.				
Address	P.O. Box 5312				
	Two Independence Way				
City	Princeton	State	NJ	Zip Code	08543
Country	United States	Telephone	609/734-9503	Fax	609/734-9700

Name (Print/Type)	Alexander J. Burke	Registration No. (Attorney/Agent)	40,425
Signature	<i>Alexander Burke</i>	Date	7 September 1999

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

5

This is a non-provisional application of provisional application serial No. 60/138,232 by K. Ramaswamy et al, filed 9th June 1999.

10

This invention is related to the field of digital signal processing, and more particularly to a trellis decoder suitable for decoding multiple mode
15 trellis encoded High Definition Television (HDTV) type signals, for example.

In broadcast and communication applications, trellis coding is employed to improve signal noise immunity. Trellis coding is used in combination with other techniques to protect against particular noise sources. One of these techniques is data interleaving, which is used to protect against interference bursts that may occur during transmission. In this technique, data is arranged (interleaved) in a prescribed sequence prior to transmission, and the original sequence is restored (deinterleaved) upon reception. This operation spreads or disperses the data in time in a predetermined sequence, such that a data loss during transmission does not result in a loss of contiguous data. Instead, any data lost is dispersed and is therefore more easily concealed or corrected. Another technique used to provide interference immunity is interference rejection filtering, which may be used to protect a signal against data dependent cross-talk and co-channel interference.

Trellis coding requirements for high definition television in the United States are presented in sections 4.2.4-4.2.6 (Annex D), 10.2.3.9, 10.2.3.10 and other sections of the *Digital Television Standard for HDTV Transmission* of April 12 1995, prepared by the United States Advanced Television Systems Committee (ATSC) (hereinafter referred to as the HDTV Standard). The HDTV Standard presents a trellis coding system that employs an interleaving function involving 12 parallel trellis encoders at a transmitter and 12 parallel trellis decoders at a receiver for processing 12 interleaved

5 datastreams. The HDTV Standard trellis coding system also employs an interference rejection filter at a receiver decoder to attenuate cross-talk and co-channel interference associated with NTSC frequencies. The rejection filter as specified by the HDTV Standard is optional and may be applied dynamically depending on the particular data being decoded.

10 The use of an interleaved code or dynamically selectable filter functions together with trellis decoding introduces additional trellis decoder design constraints and operating modes. These additional design constraints and operating modes significantly complicate the design and implementation of the trellis decoding function for HDTV receiver applications, for example. In
15 particular, complications arise when the trellis decoder is required to provide seamless switching between multiple modes, such as may occur when switching between NTSC filtered and non-filtered input data or when switching between HDTV program channels, for example. In addition, cost and hardware constraints associated with consumer HDTV receivers require an
20 efficient cost-effective trellis decoder design. Such a cost-effective design solution would employ an efficient trellis decoder architecture capable of accommodating interleaved datastreams and multiple modes of operation.

Summary of the Invention

25 In accordance with the principles of the present invention, a trellis decoder system uses a feed-forward trellis demapping configuration to prevent error propagation. In a system for processing encoded binary data symbols representable as a symbol constellation, a decoder includes a delay for
30 delaying received encoded symbol data. The decoder also includes a re-encoder for re-encoding decoded symbol representative data and a processor for deriving decoded symbol data. The processor derives decoded symbol data using the delayed encoded symbol data and re-encoded data representative of a difference between successive symbols computed using an error propagation-
35 free, feed-forward configuration.

Brief Description of the Drawings

In the drawing:

5 Figure 1 shows a trellis decoder system according to the invention for decoding multiple interleaved datastreams and for providing seamless switching between multiple operating modes.

 Figure 2 shows a trellis encoder, pre-coder and symbol mapper as
10 described in the HDTV Standard.

 Figure 3 is an encoder state table derived for the encoder system of Figure 2.

15 Figure 4 is a four state trellis diagram derived for trellis decoding data that has not been pre-filtered by an NTSC co-channel rejection filter.

 Figure 5 is an eight state trellis diagram derived for trellis decoding data that has been pre-filtered by an NTSC rejection filter.
20

 Figure 6 is a block diagram showing a branch metric computer architecture suitable for use in the trellis decoder of figure 1.

 Figure 7 is a diagram showing a branch metric computation unit
25 architecture suitable for use in the branch metric computer architecture of Figure 6.

 Figure 8 is a diagram showing an architecture of an individual Add-Compare-Select (ACS) unit, according to the invention, suitable for use in
30 the ACS function architecture of Figure 9.

 Figure 9 is a diagram showing an ACS function architecture, according to the invention, suitable for use in the trellis decoder of Figure 1.

35 Figure 10 is a diagram showing a traceback control unit architecture, according to the invention, suitable for use in the trellis decoder of Figure 1.

5 Figure 11 is a diagram showing a trellis demapper architecture incorporating feed-forward mapping according to the invention principles for use in the trellis decoder of Figure 1.

 Figure 12 shows a seamlessly switchable trellis decoder that
10 adaptively decodes multiple interleaved datastreams of either filtered or non-filtered data, in the context of an HDTV receiver system.

 Figure 13 shows a flowchart for a process for performing a trellis
15 traceback function used in the trellis decoding of interleaved data, according to the invention.

 Figure 14 shows a flowchart for a forward trace process used in the trellis decoding of interleaved data, according to the invention.

20 Figure 15 shows a trellis decoding process, incorporating the Figure 13 and Figure 14 processes, that implements the Figure 10 traceback control function, according to the invention.

Detailed Description of the Drawings

25 Figure 1 shows a video receiver trellis decoder system 24, according to the invention, for decoding multiple interleaved datastreams such as data encoded according to the HDTV Standard, for example. The system adaptively decodes datastreams that are pre-processed into a plurality of
30 formats (e.g. a normal 8-level format and a partial response 15-level format), and that are also pre-processed in one of a plurality of modes (filtered or non-filtered modes). The system also provides seamless Viterbi decoder switching between the filtered and non-filtered data modes. In addition, decoder 24 of Figure 1 uses a single adaptive trellis decoder function rather than a plurality of
35 parallel trellis decoders as portrayed in the HDTV Standard.

 Although the disclosed system is described in the context of an HDTV receiver system, it is exemplary only. The disclosed system may be used in other types of communication systems. The system may also be used in other types of operating modes involving other types of pre-processing modes

5 and functions, other types of filter functions and various data interleaving methods as well as other ways of enhancing signal noise immunity.

In overview, in Figure 1, trellis encoded input data DATA1 from a demodulator (not shown) is input to synchronization control unit 10. DATA1 is in the form of a binary data sequence of data symbols as known where each symbol is represented by an assigned digital value. The set of symbols is represented in a complex plane as a set of points called a signal constellation, as known. Unit 10 detects Field and Segment synchronization signals within DATA1. A data Field comprises a plurality of segments, each of which contains a plurality of data packets. These synchronization signals are defined by the HDTV Standard in sections 10.2.3.9-10.2.3.13 and sections 4.2.6-4.2.7 (Annex D). Unit 10 uses these detected sync signals to re-align DATA1 and to provide output re-aligned data to branch metric computer (BMC) 30 and to delay unit 70. Synchronization control unit 10 also generates register reset and register enable signals, R/E, that are used to reset and synchronize decoder 24 of Figure 1 at power-on, upon the occurrence of an out of sync condition, or in response to another input such as a global system reset, for example. Unit 10 also generates the R/E signals in response to an out-of-sync signal from synchronization monitor 80 as will be discussed later. In addition, an input signal CONF is used to configure Figure 1 system elements to decode either filtered or non-filtered data. The CONF signal indicates whether or not DATA1 has been pre-filtered by an NTSC co-channel interference rejection filter. The CONF signal may be provided by a control processor (not shown to simplify the drawing) that communicates with the Figure 1 elements for controlling the overall system functions, or it may be provided as a discrete signal from a source indicating filter presence, for example. The use of the rejection filter will be further discussed in connection with Figure 12.

Branch metric computer 30 computes a set of values (metrics) for each received data symbol. The metrics represent the proximity of a received symbol to the other points in the set that comprise the symbol constellation. The computed metrics are output to code sequence detection system 40 which employs the known Viterbi decoding algorithm. The code sequence detection system, is described in the context of an exemplary Viterbi decoding system implemented using Add-Compare-Select (ACS) unit 43 and traceback control unit 47. ACS unit 43 performs a series of repetitive add-compare-select operations using the metrics from unit 30 to provide a sequence of decision bits

5 to traceback control unit 47 and unit 30. The decision bits output by ACS unit 43 indicate the result of the add-compare-select operations on the metrics from unit 30. Traceback unit 47 uses the decision bits from unit 43 to determine for the received data symbols the most likely corresponding sequence of bits that would have been encoded by the encoder. In addition, an input decision bit
 10 from unit 43 is used in filtered mode to select between branch metric computation signal paths within the unit 30 architecture. Synchronization monitor 80 determines whether the re-aligned data output from unit 10 has been correctly synchronized by evaluating metric values from one of the add-compare-select computation units within ACS unit 43. Monitor 80 generates an
 15 out-of-sync signal for use by unit 10 and other receiver elements based on this metric value evaluation.

Traceback unit 47 outputs a sequence of trellis decoded decision bits to trellis demapper 60 and re-encoder 50. Unit 50 re-encodes the sequence of bits from unit 47 to provide a re-encoded bit sequence to demapper 60. In
 20 addition, re-aligned data from unit 10, delayed by unit 70, is provided to trellis demapper 60. Trellis demapper 60 uses the input data from units 47, 50 and 70 both to identify the transmitted data symbol, and to recover the corresponding original encoded data. The resulting recovered original data from demapper 60 is assembled into data bytes by assembler 90 and output to other receiver
 25 elements as required.

The detailed operation of the trellis decoder 24 of Figure 1 will now be discussed. In this regard it is noted that Viterbi decoding, branch metric computation and trellis coding are known and generally described, for example, in the reference text *Digital Communication*, Lee and Messerschmidt
 30 (Kluwer Academic Press, Boston, MA, USA, 1988).

The DATA1 input signal to trellis decoder 24 is encoded according to the HDTV Standard (section 4.2.5 of Annex D and other sections) using the encoding function depicted in Figure 2. Figure 2 shows that two input data bits X1 and X2 are encoded as three bits Z2, Z1 and Z0. Each
 35 three bit word corresponds to one of the 8 symbols of R. For this purpose X2 is processed by pre-coder 102, comprising filter components adder 100 and register 105, to provide encoded bit Z2, as known. X1 is encoded as two bits Z1 and Z0, as known, by trellis encoder 103 comprising adder 115 and registers 110 and 120. The output data words from the Figure 2 encoder
 40 function are mapped into a sequence of data words or symbols, R, of decimal

5 values as indicated by mapper 125 in Figure 2. The operation of the encoder of Figure 2 is illustrated by the accompanying state transition table of Figure 3.

The data output R from the encoder of Figure 2 represents a symbol constellation comprising 8 points or levels in 4 cosets. The coset values are: coset A = (A-, A+) = (-7, +1); coset B = (B-, B+) = (-5, +3); coset C = (C-, C+) = (-3, +5); and coset D = (D-, D+) = (-1, +7). This mapping is arbitrary. Other mappings, such as the 16 level mapping mentioned for cable operation in HDTV Standard section 5.1, may also be used. The data encoded in this form is modulated onto a carrier and transmitted to an HDTV receiver.

In an HDTV receiver context as shown in Figure 12, Vestigial Side Band (VSB) modulated encoded data is applied to input processor and demodulator unit 750 as will be discussed later. The demodulated data is pre-processed by a pre-processor 27 comprising NTSC co-channel interference rejection filter 22 and mux 28 before being trellis decoded. In pre-processor 27 of Figure 12, either demodulated data from unit 750 or demodulated data from unit 750 filtered by NTSC rejection filter 22 is selected by mux 28 in response to the CONF signal. The selected data from mux 28 is decoded by trellis decoder 24. Data that is not pre-filtered by unit 22 prior to trellis decoding has a data format containing 8 encoded levels further modified by any noise or interference occurring in the communication process, as known. However, data that is pre-filtered by unit 22 prior to trellis decoding has a data format containing 15 encoded levels also modified by any noise or interference occurring in the communication process, as known.

In the filtered mode when rejection filter 22 is used, an eight state trellis decoder is required, and in the non-filtered mode when filter 22 is not used, a four state trellis decoder is required, as known. Trellis decoder system 24 (Figure 1) advantageously incorporates a single eight state trellis architecture and seamlessly switches between modes. Decoder 24 provides seamless switching both for the optional filter modes and for data interruptions resulting from program changes and other types of transitions, for example. Trellis decoded data output by decoder 24 is intra-segment symbol deinterleaved by deinterleaver 755. Symbol deinterleaved data from unit 755 is then further processed by output processor 760 before being passed to other HDTV receiver elements for processing and display, as will be discussed later.

The seamless switching capability of trellis decoder 24 results both from the decoder architecture and from the design of the individual

5 decoder elements. A key feature of the architecture of decoder 24 is that it incorporates a single eight state ACS unit (unit 43) for both filtered and non-filtered data input modes. This permits Viterbi decoder 40 to transparently decode filtered or non-filtered data irrespective of the state of the CONF configuration signal. The inventors have recognized that an eight state ACS
10 unit may be used to mimic the four state ACS architecture required for the non-filtered mode. This is because BMC unit 30 performs parallel equivalent computations to provide replicated branch metric values to ACS unit 43 in the non-filtered mode. The disclosed ACS structure not only emulates the desired four state ACS architecture when it is provided with the input replicated
15 values, but also enables ACS unit 43 to operate the same way in filtered and non-filtered modes. Another feature of decoder 24 is that it incorporates an adaptive architecture responsive to input configuration signal CONF. The CONF signal indicates whether or not the decoder 24 input data is filtered by the NTSC rejection filter. These features permit decoder 24 to seamlessly
20 operate between the filtered and non-filtered modes associated with the optional use of the NTSC filter.

Control unit 10 detects the HDTV Standard compatible Field and Segment synchronization signals in input DATA1. The Field and Segment sync signals are not trellis encoded or pre-coded. Therefore the sync signals may be
25 detected using known techniques as discussed in HDTV Standard sections 10.2.3.9 and 10.3.2-10.3.3.3. These sync signals are used within unit 10 to buffer and re-align the data contained in DATA1 and to provide output re-aligned data segments, stripped of the sync information, to BMC unit 30 and to delay unit 70. The data is re-aligned by sequentially storing the data in buffer
30 registers, or equivalent memory, followed by outputting the data from the registers with the non-data sync packets omitted. The non-data packets may be removed either prior to or after storage. The encoded re-aligned data output from unit 10 is in the form of successive segments. Each segment contains successive sequential packets of the 12 interleaved datastreams (SP1-SP12).
35 Each packet contains one encoded data symbol as defined in the HDTV Standard. Neither the successive segments nor the successive packets contain intervening synchronization intervals. Alternative data re-alignment methods may be used. For example, instead of detecting and removing the sync intervals, decoder 24 may detect the sync intervals and disable or hold the

5 decoder 24 functions in a known state using reset and register enable signals for the duration of the sync intervals.

Control unit 10 also generates Reset/Enable signals, R/E, that are used to reset and synchronize decoder 24. The R/E signals are generated at both power-on and in response to a signal from synchronization monitor 80
10 indicating an out-of-sync data condition. The R/E signals may also be generated in response to an external input signal such as a global system reset or program change indication signal, for example. The architecture of decoder 24 permits re-synchronizing the trellis decoding operation in response to the R/E signals. This re-synchronizing ability enables the single trellis decoding
15 function of decoder 24 to provide seamless switching both for the optional filter modes and for data interruptions, i.e. switching that is unobjectionable to a viewer.

Control unit 10 also detects filtered data mode using the CONF signal and in this mode incorporates a further function to correct data
20 corruption caused by the NTSC rejection filter. The data corruption occurs in the four symbol packets that occur twelve symbol intervals after the Segment sync. In filtered data mode, the co-channel rejection filter subtracts an encoded data symbol of the previous data segment from a collocated (i.e. the same relative symbol packet) encoded data symbol of the current data segment. This
25 operation produces partial response input data (HDTV Standard sections 10.2.3.8 and 10.2.3.9). However, when a sync interval (four symbols in duration) precedes four symbol packets by twelve symbol intervals, the subtraction is corrupted. This is because sync values and not collocated symbol values are subtracted from these four symbol packets. Therefore unit 10, in
30 filtered data mode, identifies the four symbol packets occurring twelve symbols after the segment sync interval. In addition, unit 10 adds back the stored sync values subtracted in the rejection filter and subtracts the stored correct symbol packet data (the four collocated symbol packets that precede the segment sync). In this manner, unit 10 provides a corrected partial response re-aligned data
35 output to units 30 and 70 in filtered data mode. A similar method of correcting the partial response data is suggested in section 10.2.3.9 and Figure 10.12 of the HDTV Standard.

Branch metric computer 30 computes values (metrics) for each encoded interleaved re-aligned symbol received from unit 10. The computed
40 metrics are Viterbi decoded by unit 40 which incorporates Add-Compare-

5 Select (ACS) unit 43 and traceback control unit 47. Figure 6 shows the architecture of the branch metric computer (BMC) unit 30 of Figure 1. Figure 7 shows the architecture of an individual BMC unit of Figure 6 and is representative of each of the BMU1-BMU8 units (units 600-635). The input data provided to the S inputs of units BMU1-BMU8 of Figure 6 includes the
10 interleaved symbol data from unit 10 and inputs from the ACS unit 43 (Figure 1). The symbol data and ACS inputs (ACSI) are separately identified in Figure 7 as inputs to units 700 and 730 respectively.

The BMC unit of Figure 7 sequentially processes the encoded interleaved symbol sequence from unit 10. In a non-filtered data mode as
15 selected by the CONF signal, input symbol data of a first interleaved symbol in the data from unit 10 is passed unaltered by adder 700. In this mode multiplexer (mux) 705 outputs a zero value to adder 700. First and second distance computers 710 and 715 compute the Euclidean geometrical distance of the encoded input symbol from first and second cosets respectively and provide
20 two corresponding metric value outputs, Branch Metric Data1 and Branch Metric Data2. Table I defines the coset computation performed by each BMU unit distance computer e.g. for BMU1 proximity to cosets A and C respectively are computed. Also, first and second distance computers 710 and 715 each provide, via registers 740 and 735, output bits C and D. Bits C and D indicate
25 which one of the two values within each of the first and second cosets the input symbol is closest to. Registers 740 and 735 each comprise serially connected individual one bit registers through which bits C and D are cyclically shifted, respectively. In this manner output bits C and D for each of the 12 interleaved symbols from unit 10 (Figure 1) are sequentially output from registers 740 and
30 735. The distance computer is typically implemented using look-up tables but may also be implemented by other methods such as by computing distances with subtraction, absolute value and comparison operations, for example.

664000 0507660

5 Table I.

BMU unit	COSET DEFINITION		
	First Distance Computer	Second Distance Computer	Coset W
BMU1	A	C	A
BMU2	B	D	C
BMU3	B	D	A
BMU4	A	C	C
BMU5	C	A	B
BMU6	D	B	D
BMU7	D	B	B
BMU8	C	A	D

In the filtered data operating mode, input symbol data of a first interleaved symbol in the data from unit 10 is summed by adder 700 with either coset value W+ or coset value W- from unit 720 via muxes 725 and 705. The summed data is processed by distance computers 710 and 715 as explained before. Coset values W+ and W- belong to one of the four previously defined cosets A-D. The particular W+ and W- coset value which is used in an individual BMU unit is selected from the four defined cosets for that particular BMU unit as defined in Table I. The W+ and W- coset is chosen to restore the modified input symbol data from unit 10 to symbol data that can be processed by the distance computers 710 and 715. This operation is required in the filtered mode since the combination of interleaving and co-channel rejection filtering produces partial response input data as previously mentioned and not the normal symbol data produced in the non-filtered mode (HDTV Standard sections 10.2.3.8 and 10.2.3.9). Mux 730 via mux 725 determines whether W+ or W- is summed in adder 700 with the modified input data based on the state of the ACSI input decision bit from ACS unit 43 and the state of bit input signals A and B. The ACSI input decision bit from unit 43 determines whether input A or input B selects between the W+ and W- values that are summed by adder 700. For example, if ACSI=1, input B is selected by mux 730 and if B=1, W+ is selected by mux 725 to be added in adder 700 via mux 730. The A and B input interconnections are shown in Figure 6, for example, A and B for unit BMU4 are provided by BMU5 and BMU6 respectively (Figure 6). The remaining operation of the BMC unit of Figure 7 in the filtered mode is the same as the operation described for the non-filtered mode.

5 BMC unit 30 of Figure 1 similarly sequentially processes the remaining interleaved symbols of a re-aligned data segment from unit 10. After completely processing a re-aligned data segment, BMC unit 30 repeats the described process starting with the first interleaved data symbol packet of the next re-aligned data segment from unit 10.

10 The interconnection of the individual identical BMU units (BMU1-BMU8) is shown in the overall BMC architecture in Figure 6. Interleaved symbol data from unit 10 is input to the S inputs of units BMU1-BMU8 and is processed by each of these interconnected units as described for the exemplary unit of Figure 7. The resulting Branch Metric Data1 and Branch
15 Metric Data2 outputs on terminals V0 and V1 of units BMU1-BMU8 are provided to ACS unit 43 (Figure 1). ACS unit 43 of Figure 1 performs a series of repetitive add-compare-select operations using the Branch Metric Data1 and Branch Metric Data2 outputs from each of the BMU units of unit 30.

Figure 9 shows the interconnections between the individual ACS
20 units that comprise the overall ACS architecture of unit 43 of Figure 1. In Figure 9 a single eight state ACS architecture is used for both filtered and non-filtered data input modes. The Figure 9 ACS architecture implements the filtered mode eight state transition diagram of Figure 5. Each ACS unit (units 900-935) is associated with a trellis state (000...111). The four state transition
25 diagram of Figure 4 shows the equivalent trellis state transitions for the non-filtered mode. Re-ordering of the states shown in the state transition diagram of Figure 5 further clarifies the interconnections shown in Figure 9.

Figure 8 shows the architecture of an individual ACS unit representative of each of the Figure 9 ACS units (units 900-935). The Figure 9
30 ACS architecture sequentially processes the branch metric data for the individual interleaved data symbols from unit 30 (Figure 1). Adders 805 and 810 of Figure 8 sum input Path Metric Data1 and input Path Metric Data2 obtained from other ACS units with the Branch Metric Data1 and Branch Metric Data2 outputs for an interleaved data symbol from BMU unit 30 (Figure
35 1). The two resultant data sums from units 805 and 810 are compared by unit 815. A single decision bit output indicating which of the two sums is the smaller is output by unit 815 to register 800 and to mux 820. Mux 820 selects the smaller sum from the outputs of units 805 and 810. This selected sum appears as Output Path Metric Data at the output of register 825.

5 Register 800 comprises twelve serially connected individual one bit registers through which the decision bit output from unit 815 is cyclically shifted. The decision bit output provided as the ACSI output to unit 30 (Figure 1) follows a twelve cycle delay by register 800. The decision bit output provided to traceback control unit 47 (Figure 1) follows a single cycle delay by
 10 register 800. In this manner each single decision bit output associated with each of the 12 interleaved symbols is sequentially output from register 800. Similarly, register 825 comprises serially connected individual registers through which the Output Path Metric Data from unit 820 is cyclically shifted. In this manner the Output Path Metric Data associated with each of the 12
 15 interleaved symbols is sequentially output from register 825. The bit width of the serially connected registers within unit 825 is selected in accordance with ACS unit processing resolution requirements.

The Output Path Metric Data from register 825 is provided to two other ACS units in accordance with the interconnection diagram of Figure
 20 9. For example, the Output Path Metric Data from ACS unit 900 of Figure 9 is provided to the input Path Metric Data1, V2, inputs of ACS units 910 and 915. Similarly, input Path Metric Data1 and input Path Metric Data2 provided to adders 805 and 810 of Figure 8 are provided by two other ACS units in accordance with the interconnection diagram of Figure 9. For example, the
 25 Input Path Metric Data1, V2, input of ACS unit 900 is provided by ACS unit 905 and the input Path Metric Data2, V3, input of ACS unit 900 is provided by ACS unit 925. The sequence of decision bits indicating the result of the sequence of add-compare-select operations on the metrics from unit 30 (Figure 1) are output from register 800 of Figure 8 to traceback control unit 47
 30 following a single cycle delay and to unit 30 (Figure 1) following a twelve cycle delay. Each of the eight ACS units of unit 43 provides a sequence of decision bits to units 47 and 30. Eight decision bits are cyclically output in parallel from unit 43 to units 47 and 30 for each of the interleaved symbol packets provided by unit 10. BMC unit 30 and ACS unit 43 (Figure 1) are
 35 interconnected as indicated in Table II. Units 30 and 43 are shown in Figures 6 and 9, respectively.

Table II

OUTPUT	CONNECTED TO INPUT
BMU1-V0	V0-ACS unit 905
BMU1-V1	V0-ACS unit 900

BMU2-V0	V0-ACS unit 915
BMU2-V1	V0-ACS unit 910
BMU3-V0	V1-ACS unit 915
BMU3-V1	V1-ACS unit 910
BMU4-V0	V1-ACS unit 905
BMU4-V1	V1-ACS unit 900
BMU5-V0	V0-ACS unit 925
BMU5-V1	V0-ACS unit 920
BMU6-V0	V0-ACS unit 935
BMU6-V1	V0-ACS unit 930
BMU7-V0	V1-ACS unit 935
BMU7-V1	V1-ACS unit 930
BMU8-V0	V1-ACS unit 925
BMU8-V1	V1-ACS unit 920
ACSI unit 900	BMU2-ACSI
ACSI unit 905	BMU1-ACSI
ACSI unit 910	BMU6-ACSI
ACSI unit 915	BMU5-ACSI
ACSI unit 920	BMU3-ACSI
ACSI unit 925	BMU4-ACSI
ACSI unit 930	BMU7-ACSI
ACSI unit 935	BMU8-ACSI

5

In the non-filtered mode, there are a maximum of four distinct branch metric values for a given received non-filtered symbol. Also, in this mode BMC unit 30 performs sixteen parallel computations to provide sixteen branch metric values to ACS unit 43, and a single computation is replicated
 10 four times. Therefore, the sixteen values provided to unit 43 include replications of the four distinct branch metric values. The replication of the branch metric values that are input to unit 43 enables the architecture of ACS unit 43 (Figure 9) to emulate the desired four state ACS trellis of Figure 4. Note, in practice, branch metric values are substantially, rather than perfectly,
 15 replicated by BMC unit 30 due to system noise.

In the filtered mode, BMC unit 30 (Figure 1) generates a maximum of fifteen distinct branch metric values for each input symbol and operates according to the eight state ACS trellis of Figure 5. The use of a single eight state ACS architecture, as shown in Figure 9, for both filtered and non-
 20 filtered input modes facilitates the seamless and transparent transition of trellis decoder 24 between the modes.

5 The Most Significant Bit (MSB) of the Output Path Metric Data from register 825 (Figure 8) of one of the ACS units (units 900-935 of Figure 9) is also provided to synchronization monitor 80 (Figure 1). Synchronization monitor 80 counts the number of inversions in the MSB from register 825 that occur in a programmed time interval, and compares the count against a
10 programmed threshold value. The programmed value may be provided by a control processor (not shown) or stored in unit 80. If the count exceeds the threshold value, an out-of-sync indication signal is generated and provided to Synchronization control unit 10 (Figure 1). Upon receipt of an out-of-sync signal from unit 80, unit 10 provides a reset signal to unit 80 to reset the
15 synchronization monitor to permit detection of another out-of-sync condition. Monitor 80 may be alternatively arranged to respond to different parameters.

 The architecture of ACS unit 43 provides decision bit data to traceback unit 47 (Figure 1) organized both by interleaved data symbol and by ACS unit trellis state. Traceback unit 47 cyclically receives eight decision bits
20 in parallel (B1-B8, one 8 bit word) from the corresponding eight ACS units of unit 43 for each of the encoded interleaved symbols provided by unit 10. One eight bit word is cyclically received per interleaved symbol. The received decision words represent eight sequences of decision bits from the corresponding eight ACS units of unit 43. Unit 47 sequentially processes each
25 decision word from unit 43 associated with an individual interleaved data symbol. Decision words are used by unit 47 to produce the most likely sequence of Z1 bits representing the interleaved symbol sequence previously encoded at the transmitter. Each decision bit identifies which of the two possible state transition paths lead to an ACS unit state.

30 Figure 10 shows the architecture of Traceback Control unit 47 (Figure 1). The operation of traceback unit 47 will be described for decision words associated with a sequence of encoded interleaved symbols output by ACS unit 43. The traceback architecture of Figure 10 implements the trellis decoding process depicted in Figure 15. In step 443 of Figure 15, following the
35 start at step 440, decision words are cyclically input in the form of eight decision bit sequences from ACS unit 43 (Figure 1). The input decision words are provided to forward trace unit 160 (Figure 10) and, in step 445, are also stored and delayed in buffer memory 140 (Figure 10). In step 450, traceback select unit 145 of Figure 10 derives eight trellis decoded bit sequences from the
40 decision bit sequences stored in unit 140. These trellis decoded bit sequences

5 are candidates for the most likely encoded Z1 bit sequence corresponding to the encoded interleaved data symbols.

In step 450 of Figure 15, unit 145 (Figure 10) derives the candidate decoded Z1 bit sequences by determining state transition trellis paths in a traceback process. In this process, an initial antecedent trellis state is identified for the current state of one of the eight decision bit input sequences. This initial state is identified by using a decision bit from ACS unit 43 (Figure 1) in the input sequence as an indicator of an antecedent transition path. From this initial antecedent state, other antecedent states are identified by traversing the trellis state transition diagram in reverse direction using the decision bits from ACS unit 43 until a sequence of antecedent states has been identified. From this sequence of antecedent states a corresponding sequence of trellis decoded bits is determined. These steps are repeated for each of the remaining sequences of decision bits stored in buffer 140 (Figure 10). The theory behind the traceback process is known and is described with other different traceback methods in *Architectural Tradeoffs for Survivor Sequence Memory Management in Viterbi Decoders* by G. Feygin et al published in the I.E.E.E. Transactions on Communications, vol. 41, No. 3, March 1993.

The described traceback process is performed to a predetermined depth T, the traceback depth, to identify a predetermined number of antecedent states. In accordance with known theory, traceback interval T is adopted in practice as a sufficient interval of traceback to identify a merged or converged state (Lee and Messerschmidt, section 7.4.3). The merged state is the state that is likely to be reached following traceback from any initial antecedent trellis state. The merged state identifies the data sequence with the greatest likelihood of being the true encoded Z1 data. Therefore, the merged state indicates the trellis decoded data sequence that is to be output from the candidate sequences. The traceback process, in the exemplary embodiment, is performed in two stages for traceback intervals, termed Epochs, equal to $\frac{T}{2}$. The selection of such Epochs or sub-traceback intervals is arbitrary and selectable by a system designer.

In order to identify the candidate decoded trellis sequences, traceback is performed on collocated interleaved symbol packets of successive re-aligned data segments. Traceback on one of the twelve interleaved symbol packets, for example packet seven (SP7), is performed to identify antecedent

5 states for symbol data in the corresponding prior, here seventh (SP7), interleaved symbol packets.

Although traceback on a single trellis path is known, the disclosed system advantageously extends the traceback process to encompass traceback for interleaved data and for a plurality of candidate decision bit
 10 sequences. This extended traceback process is performed on an Epoch by Epoch basis using the method of Figure 13 which is implemented by unit 145 of Figure 10. In step 645 of Figure 13, following the start at step 640, internal storage registers within traceback select unit 145 are initialized at an Epoch data boundary in response to control signals from control unit 165 (Figure 10).
 15 A decision word for an interleaved symbol packet, e.g. SP1, is cyclically input at step 650 from buffer 140 (Figure 10). An antecedent state is identified from the current state in step 655 by applying the previously described traceback process using a decision bit, e.g. B1, of the decision word input in step 650. A key feature of the process is that the antecedent state is identified for symbol
 20 data of collocated interleaved packets of successive data segments. For example, for the seventh interleaved symbol packet (SP7) of a data segment, a corresponding seventh interleaved symbol packet decision bit is used to identify an antecedent state. In step 655 a trellis decoded bit corresponding to the identified antecedent state of the interleaved symbol is stored in memory
 25 150 by unit 145 (Figure 10).

Step 660 repeats step 655 for each of the remaining decision bits (B2-B8 in the example) of the input decision word until eight trellis decoded bits for the interleaved symbol have been stored in memory 150 (Figure 10). In step 665, steps 650-660 are repeated for each of the remaining twelve
 30 interleaved symbols (SP2-SP12 in the example) of a re-aligned data segment. Similarly, steps 650-665 are repeated in step 670 for the number of re-aligned data segments that comprise an Epoch interval. In step 675, the resulting eight candidate trellis decoded bit sequences for the input interleaved symbols are provided by unit 145 to memory 150 of Figure 10. This iteration of the
 35 traceback process for one Epoch interval ends at step 680 of Figure 13 and completes step 450 of the encompassing process of Figure 15.

In steps 460 and 465 of Figure 15, forward trace unit 160 (Figure 10) identifies the trellis decoded bit sequence in the eight candidate sequences that most likely corresponds to the sequence that was encoded and transmitted
 40 to the receiver. In step 470, the resulting identified trellis decoded sequence,

5 following a delay, is provided by memory 150 to trellis demapper 60 and re-
encoder 50 (Figure 1) via mux 155 in response to a selection signal from trace
unit 160.

In steps 460 and 465 of Figure 15, trace unit 160 identifies the merged state and the trellis decoded bit sequence that most likely corresponds with the transmitted interleaved symbol packet sequence. Trace unit 160 identifies the trellis decoded bit sequence on an Epoch by Epoch basis using the forward trace process shown in Figure 14. The forward trace technique is a cost-effective method of reducing data decoding delay (latency).

15 In step 460 of Figure 15, the Figure 14 forward trace process is performed for an Epoch interval of input data to update two pointers, pointer1 and pointer2, for each of the eight data sequences. These pointers are used to identify the trellis decoded bit sequence.

In step 843 of Figure 14, following the start at step 840, the eight pointer2 indicators are updated with corresponding pointer1 indicator values. These pointers are stored within unit 160. In step 845, internal storage registers within unit 160 are initialized at an Epoch data boundary in response to control signals from control unit 165 (Figure 10). Control unit 165 provides control signals in response to the R/E input signals from unit 10 (Figure 1) for synchronizing both trace units 145 and 160 to start tracing at an Epoch boundary. A non-delayed decision word for an interleaved symbol packet, e.g. SP1, is cyclically input at step 850 from ACS unit 43 (Figure 1).

In step 855, a three stage procedure is used to update one of eight separate pointer1 indicators that are associated with the eight data sequences of the input decision words. A decision bit, e.g. B1, of the input non-delayed word is used to identify an antecedent state from the current state by applying the previously described traceback process. The antecedent state is identified for symbol packet data of a collocated interleaved symbol packet (SP1 in the example) of a preceding data segment as described for the traceback process of unit 145. The identified antecedent state is used to select one of the eight separate pointer1 indicators that are associated with the eight data sequences of the input decision words. The state indicated by the selected pointer1 of the interleaved symbol (SP1 of the example) is stored in the pointer1 indicator associated with the decision bit sequence (the sequence for B1 in the example) overwriting any previous pointer1 contents.

5 X1 bits of the interleaved symbols that were encoded by the encoder of Figure 2. Note, the X1 bit sequence is equal to the Z1 bit sequence as shown in Figure 2. The steps of the Figure 15 process are repeated as long as there is available input decision data. The process otherwise terminates at step 480.

Unit 50 (Figure 1) sequentially re-encodes the interleaved Z1
 10 sequence of bits from unit 47 (and mux 155 of Figure 10) to provide a re-encoded Z0 bit sequence to demapper 60. The re-encoding function used to produce Z0 from Z1 duplicates the equivalent function performed in the encoder prior to transmission as depicted in Figure 2. In addition, re-aligned interleaved symbol data from unit 10, delayed and synchronized to the output
 15 of unit 47 by unit 70, is provided to trellis demapper 60. Figure 11 shows the architecture of trellis demapper 60 (Figure 1). Trellis demapper 60 sequentially processes the synchronized interleaved data sequences from units 47, 50 and 70 (Figure 1).

In describing and interpreting Figure 11, the following
 20 convention is adopted. The data representing the 8 point symbol constellation described in connection with Figure 2 and comprising the 4 cosets, coset A = (A-, A+); coset B = (B-, B+); coset C = (C-, C+); and coset D = (D-, D+) are represented in the time domain in the form of subset values S_n , S_{n-1} , and S_{n+1} , where n is a time index. These subset values represent coordinate pair values,
 25 specifically, $S_n=(S_n^-, S_n^+)$ for a current symbol time period n , $S_{n-1}=(S_{n-1}^-, S_{n-1}^+)$ for the immediately prior symbol time period $n-1$, and $S_{n+1}=(S_{n+1}^-, S_{n+1}^+)$ for the immediately succeeding symbol time period $n+1$.

Demapper 60 uses units 950-980 to decode information bits of the symbol coordinate representative subsets using a state machine that
 30 advantageously uses past subset outputs instead of decoded bits themselves. This avoids a problem of error propagation involved in the feedback of past subsets and/or past decoded bits.

In a conventional trellis demapper, re-encoded data (e.g. from unit 50) together with delayed received data (e.g. from unit 70) is used to
 35 determine the output bit X2. The inventors have recognized that in such a conventional demapper (and in other decoding applications) catastrophic error propagation may result from cumulative error feedback. This occurs under a variety of conditions including, for example, in filtered data mode when NTSC co-channel interference rejection filter (unit 22 of Figure 12) is active.
 40 Demapper 60 of Figure 11 advantageously avoids such catastrophic error

5 propagation by employing a feed-forward technique involving the feed-forward of prior state or decoded outputs rather than the feedback of intermediate state or decoded data. This technique is applicable to any partial response or other decoding system involving error determination and time domain decision making for deriving the best possibility from multiple candidate possibilities.

10 In Figure 11, re-encoded data representing two possible constellation points in the form of current subset values, S_n , is provided by re-encoder 50 to subset difference computer 960. In addition, re-encoded data from unit 50 is delayed by 1 symbol period by unit 950 via multiplexer 955 in order to generate delayed subset values S_{n-1} which are also provided to
 15 computer 960. In non-filtered data mode, the previous subset values S_{n-1} provided to computer 960 are set to zero via multiplexer 955 and delay 950 in response to the CONF signal. Unit 960 computes the four types of differences between the coordinate pairs of subsets S_n and S_{n-1} i.e. unit 960 computes, $(S_n^- - S_{n-1}^-)$, $(S_n^- - S_{n-1}^+)$, $(S_n^+ - S_{n-1}^-)$, $(S_n^+ - S_{n-1}^+)$. These four computed outputs are
 20 provided by computer 960 to constellation distance computer 965 which computes the absolute distance of each computed subset difference from the corresponding delayed data input f_n from unit 70. The four computed subset differences from unit 965 are processed by comparators 973, 971 and 964 in conjunction with multiplexers 963 and 977 in order to identify the smallest
 25 subset difference from the delayed data f_n . For this purpose, comparators 973 and 971 respectively provide min_minus and min_plus intermediate constellation distance difference values via multiplexers 963 and 977 to final comparator 964.

Demapper 60 derives a resultant output X2 bit value by different
 30 methods depending on whether or not unit 965 provides a single computed subset difference as a minimum value indicating that there is no decision ambiguity. This is the most likely case and occurs when only one of the four signals output by unit 965 comprises a minimum distance value. In this case, unit 964 declares the current demapped bit as the demapped output bit X2p.
 35 For this purpose, unit 964 determines the smaller of the min_minus input from unit 963 and the min_plus input from unit 977. If the min_minus input is the smallest, the demapped bit X2p is set to zero. If the min_plus input is the smallest, the demapped bit X2p is set to 1. This bit output convention is determined to provide conformity with the original signal mapping as
 40 previously described in connection with Figures 2 and 3. Consequently, X2p is

5 advantageously derived using feed-forward of past subset outputs instead of feedback of decoded bits or subset outputs thereby avoiding cumulative error propagation.

10 In the case that more than one of the four signal output values from unit 965 are equal and comprise the minimum distance value, a decision ambiguity occurs. In this case, the previous output of unit 964 (i.e. the output of unit 964 delayed by the delay element 975) is compared by unit 964 with the min_minus_dec signal output by comparator 973. If these two outputs are the same, the demapped bit X2p is set to zero, otherwise bit X2p is set to one. In other embodiments, the min_plus_dec signal output by comparator 971 may
15 alternatively be used for this purpose. It is to be noted that, although a delayed decision bit is being fed back from unit 975 to unit 964 to resolve the decision ambiguity, this does not result in error propagation. This is because a previous decoded output is only used to produce a future output in the case of equality between computed subset differences produced by unit 965. Once this equality
20 is resolved, unit 965, in normal operation, produces a unique value as the minimum distance value in the next cycle thereby preventing repetitive feedback of decoded outputs and eliminating feedback mechanism induced error propagation. The final demapped output bit X2 is produced by unit 980 exclusively-ORing X2p (the current output of unit 964) with the previous
25 output of 964 produced by unit 975.

Demapper 60 (Figure 1) provides the resulting recovered X2 data together with synchronized X1 data to assembler 90. An X1 bit and an X2 bit corresponding to each interleaved data symbol that is input to decoder 24 are sequentially provided by unit 60 to assembler 90. Each X1, X2 bit pair is the
30 trellis decoded data for a symbol packet. Assembler 90 assembles four X1, X2 bit pairs for collocated interleaved packets of successive data segments into one eight bit byte. Unit 90 assembles data bytes in this way for each of the twelve interleaved symbol packets. Unit 90 outputs the bytes on a byte by byte basis for each of the twelve interleaved symbol packet streams. In this manner unit
35 90 provides intra-segment symbol deinterleaved output data for use by remaining receiver elements.

In an exemplary HDTV receiver system shown in part in Figure 12, encoded data is processed and demodulated by processor and demodulator 750. Unit 750 includes an input channel tuner, RF amplifiers, an IF
40 (Intermediate Frequency) amplifier and mixer stage, for down converting the

5 modulated signal to a lower frequency band suitable for further processing. Input processor 750 also includes an automatic gain control network, analog to digital converter, and timing and carrier recovery networks. The received signal is demodulated to baseband by the carrier recovery network within unit 750. The carrier recovery network may employ equalizer, rotator, slicer and phase
10 error detector networks as well as a phase controller for controlling the equalizer and rotator operation, as known.

Either the demodulated data or the demodulated data processed by NTSC rejection filter 22 is selected by mux 28 in response to the CONF signal and decoded by decoder 24, according to the invention. Trellis decoded and
15 intra-segment symbol deinterleaved data output by decoder 24 is provided to unit 760. Symbol deinterleaved data from decoder 24 is convolutionally inter-segment deinterleaved and Reed-Solomon decoded by output processor 760 before being passed to other HDTV receiver elements for further processing and display. The intra-segment deinterleaving process associated with trellis
20 coding is distinct and different from the inter-segment deinterleaving process (HDTV Standard sections 10.2.3.9 and 10.2.3.10). The functions discussed in connection with units 750 and 760 are described, for example in the Lee and Messerschmidt text previously mentioned, among others.

The architectures discussed with respect to Figures 1-15 are not
25 exclusive. Other architectures may be derived in accordance with the principles of the invention to accomplish the same objectives. For example, either a single trellis decoder may be used to decode N packets of input data, or more than one trellis decoder may be used (e.g. less than N) depending on the requirements of a particular system. In addition, architecture may be devised
30 with different numbers of trellis transition states. The principles of the invention are not restricted to the described eight state architecture. Further, the functions of the elements of the various architectures may be implemented in whole or in part within the programmed instructions of a microprocessor.

5 What is claimed is:

1. In a system for processing encoded data symbols representable as a symbol constellation, a method for providing decoded symbol data comprising the steps of:

10 delaying received encoded symbol data to produce delayed data;
 re-encoding decoded symbol representative data to produce re-
encoded data;
 feed-forward processing said re-encoded data to produce
difference data representative of a difference between successive symbols; and
15 deriving decoded symbol data using said delayed data and said
difference data.

2. A method according to claim 1, wherein
said feed-forward processing is exclusive of feed-back
20 processing.

3. A method according to claim 1, wherein
said feed-forward processing prevents error accumulation
induced by error-propagation resulting from feed-back processing.

4. A method according to claim 1, including the steps of
comparing candidate values representative of distance between,
said delayed received encoded symbol data, and said difference data, to
determine minimum distance values, and
30 resolving equality between candidate minimum distance values in
response to a prior delayed and fed back comparison representative output.

- 5 5. In a system for processing encoded data symbols representable
as a symbol constellation, a decoder comprising:
 a delay for delaying received encoded symbol data to produce
 delayed data;
 a re-encoder for re-encoding decoded symbol representative data
10 to produce re-encoded data; and
 a processor for,
 feed-forward processing said re-encoded data to produce
 difference data representative of a difference between successive symbols; and
 deriving decoded symbol data using said delayed data and
15 said difference data.
6. A decoder according to claim 5, wherein
 said feed-forward processing is exclusive of feed-back
20 processing.
7. A decoder according to claim 5, wherein
 said feed-forward processing prevents error accumulation
induced by error-propagation resulting from feed-back processing.
- 25 8. A decoder according to claim 5, wherein
 said processor includes a decision processor for deriving said
decoded symbol data by computing an absolute distance between, said
difference data, and a corresponding delayed received encoded symbol.
- 30 9. A decoder according to claim 5, wherein said processor
includes,
 a decision processor for deriving said decoded symbol data by
computing an absolute distance using said difference data and said delayed
data, and
35 a comparator for comparing computed absolute distance values to
determine a minimum symbol difference value.

5 10. A decoder according to claim 5, wherein said processor includes,

 a decision processor for comparing candidate values representative of distance between, said delayed data, and said difference data, to determine minimum distance values and resolving equality between
10 candidate minimum distance values in response to a prior delayed and fed back comparison representative output.

 11. A decoder according to claim 10, wherein
 said prior delayed fed back comparison representative output is
15 only used in the case of equality between candidate minimum distance values.

 12. A decoder according to claim 5, wherein
 said processor derives decoded symbol data in a partial response
system.
20

 13. In a system for processing encoded data symbols represented in a complex plane as a set of points called a symbol constellation, a decoder comprising:

 a delay for delaying received encoded symbol data to produce
25 delayed data;

 a re-encoder for re-encoding decoded symbol representative data to produce re-encoded data; and

 a processor including,
 a feed-forward processor for processing said re-encoded
30 data exclusively of feed-back processing in order to produce difference data representative of a difference between successive symbols; and

 a decision processor for deriving said decoded symbol data by computing an absolute distance using said difference data and said delayed data.
35

 14. A decoder according to claim 13, wherein said processor includes,

 a comparator for comparing computed absolute distance values to determine a minimum symbol difference value.
40

5 15. A decoder according to claim 13, wherein said processor includes,

 a comparator for comparing candidate values representative of distance between, said delayed data, and said difference data, to determine minimum distance values and resolving equality between candidate minimum
10 distance values in response to a prior delayed and fed back comparison representative output.

 16. A decoder according to claim 15, wherein said processor uses a different configuration in resolving equality between candidate distance
15 values than is used for deriving said difference data.

 17. A decoder according to claim 13, wherein state machine state representative outputs represent said difference data.

20 18. In a system for processing trellis encoded data, trellis decoding apparatus comprising:

 a delay for delaying received trellis encoded data to produce delayed data;

 a re-encoder for re-encoding decoded trellis encoded data using
25 decision data associated with trellis state transitions in response to said trellis encoded data to produce re-encoded subset data;

 a processor for,
 feed-forward processing said re-encoded subset data to produce subset difference data representative of a difference between
30 successive symbols using past subset outputs in an error propagation-free, feed-forward configuration; and

 deriving decoded symbol data using said delayed data and said difference data.

35 19. A decoder according to claim 18, wherein
 said error propagation-free feed-forward configuration of said processor derives decoded symbol data using past subset outputs instead of decoded bits themselves.

40

5

Abstract

A trellis decoder system uses a feed-forward trellis demapping configuration to prevent error propagation. In a system for processing encoded binary data symbols representable as a symbol constellation, a decoder
10 includes a delay for delaying received encoded symbol data. The decoder also includes a re-encoder for re-encoding decoded symbol representative data and a processor for deriving decoded symbol data. The processor derives decoded symbol data using the delayed encoded symbol data and re-encoded data representative of a difference between successive symbols computed using an
15 error propagation-free, feed-forward configuration.

002060 65075660

FIGURE 1.




FIGURE 2.




FIGURE 3.

INPUT & FEEDBACK	CURRENT STATE	NEXT STATE	ENCODER OUTPUT
X_1 Y X_2	S_0 S_1	S_0 S_1	Z_2 Z_1 Z_0
0 0 0	0 0	0 0	0 0 0
0 0 1	0 1	1 0	1 0 1
0 1 0	1 0	0 1	1 0 0
0 1 1	1 1	1 1	0 0 1
1 0 0	0 0	0 1	0 1 0
1 0 1	0 1	1 1	1 1 1
1 1 0	1 0	0 0	1 1 0
1 1 1	1 1	1 0	0 1 1

FIGURE 4.




FIGURE 5.




FIGURE 12




FIGURE 6.




FIGURE 7.




FIGURE 8.




FIGURE 9.





FIGURE 10.






FIG. 11

FIGURE 13




FIGURE 14





FIGURE 15



DECLARATION AND POWERS OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

CODE MAPPING IN A TRELLIS DECODER

the specification of which was filed on Herewith as Application Serial No. _____ and was amended on _____, or, if not identified here by filing date and serial number, is attached hereto.

I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 USC 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate by me or my representatives or assigns for this invention having a filing date before that of the application on which priority is claimed.

Application No. -- _____ in -- _____ on -- _____ priority claimed () Yes () No

Application No. -- _____ in -- _____ on -- _____ priority claimed () Yes () No

Application No. -- _____ in -- _____ on -- _____ priority claimed () Yes () No

I hereby claim the benefit under 35 USC 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 USC 112, I acknowledge the duty to disclose material information as defined in 37 CFR 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application

Serial No. -- _____ Filed -- _____ () patented () pending () abandoned

Serial No. -- _____ Filed -- _____ () patented () pending () abandoned

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 USC 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint, individually and collectively, the following as my/our attorney or agent with full power of substitution and revocation, to prosecute this application and to transact all business in the U.S. Patent and Trademark Office connected therewith:

Joseph S. Tripoli Registration No. 26,040 and

Ronald H. Kurdyla Registration No. 26,932 and

Alexander J. Burke Registration No. 40,425 and

Registration No. _____

PLEASE ADDRESS ALL

COMMUNICATIONS TO: JOSEPH S. TRIPOLI

PATENT OPERATIONS

THOMSON multimedia Licensing Inc.

PO Box 5312

PRINCETON, NEW JERSEY 08543-5312

Sole or Joint Inventor (1)	<u>VASUDEVAN PARTHASARATHY</u> (Type or Print)	<u>X</u> (Signature in Full. No initials.)
Citizenship	<u>India</u>	Date <u>29th July, 1999</u>
Post Office Address	<u>8638 Algeciras Drive - 1C, Indianapolis, Indiana 46250</u>	
Residence	<u>Indianapolis (Marion County), Indiana 46250</u>	
Sole or Joint Inventor (2)	<u>KUMAR RAMASWAMY</u> (Type or Print)	<u>X</u> (Signature in Full. No initials.)
Citizenship	<u>India</u>	Date <u>29th July, 1999</u>
Post Office Address	<u>9417 College Drive #B, Indianapolis, Indiana 46240</u>	
Residence	<u>Indianapolis (Marion County), Indiana 46240</u>	
Sole or Joint Inventor (3)	<u>JOHN SIDNEY STEWART</u> (Type or Print)	<u>X</u> (Signature in Full. No initials.)
Citizenship	<u>USA</u>	Date <u>7-30-99</u>
Post Office Address	<u>3655 W. 71st Street, Indianapolis, Indiana 46268</u>	
Residence	<u>Indianapolis (Marion County), Indiana 46268</u>	

Express Mail Label: EL278371849US

RCA 88,495

DECLARATION AND POWERS OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

CODE MAPPING IN A TRELIS DECODER

the specification of which was filed on Herewith as Application Serial No. _____ and was amended on _____, or, if not identified here by filing date and serial number, is attached hereto.

I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 USC 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate by me or my representatives or assigns for this invention having a filing date before that of the application on which priority is claimed.

Application No. -- _____ in -- _____ on -- _____ priority claimed ☐ Yes ☐ No

Application No. -- _____ in -- _____ on -- _____ priority claimed ☐ Yes ☐ No

Application No. -- _____ in -- _____ on -- _____ priority claimed ☐ Yes ☐ No

I hereby claim the benefit under 35 USC 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 USC 112, I acknowledge the duty to disclose material information as defined in 37 CFR 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application

Serial No. -- _____ Filed -- _____ ☐ patented ☐ pending ☐ abandoned

Serial No. -- _____ Filed -- _____ ☐ patented ☐ pending ☐ abandoned

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 USC 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint, individually and collectively, the following as my/our attorney or agent with full power of substitution and revocation, to prosecute this application and to transact all business in the U.S. Patent and Trademark Office connected therewith:

<u>Joseph S. Tripoli</u>	Registration No. <u>26,040</u>	and
<u>Ronald H. Kurdyla</u>	Registration No. <u>26,932</u>	and
<u>Alexander J. Burke</u>	Registration No. <u>40,425</u>	and
	Registration No. _____	

PLEASE ADDRESS ALL

COMMUNICATIONS TO: JOSEPH S. TRIPOLI

PATENT OPERATIONS

THOMSON multimedia Licensing Inc.

PO Box 5312

PRINCETON, NEW JERSEY 08543-5312

Sole or Joint Inventor (1)	<u>VASUDEVAN PARTHASARATHY</u> (Type or Print)	X <u>[Signature]</u> (Signature in Full. No initials.)
Citizenship	<u>India</u>	Date <u>8/19/1999</u>
Post Office Address	<u>8638 Algeciras Drive - 1C, Indianapolis, Indiana 46250</u>	
Residence	<u>Indianapolis (Marion County), Indiana 46250</u>	
Sole or Joint Inventor (2)	<u>KUMAR RAMASWAMY</u> (Type or Print)	X <u>[Signature]</u> (Signature in Full. No initials.)
Citizenship	<u>India</u>	Date <u>29th July, 1999</u>
Post Office Address	<u>9417 College Drive #B, Indianapolis, Indiana 46240</u>	
Residence	<u>Indianapolis (Marion County), Indiana 46240</u>	
Sole or Joint Inventor (3)	<u>JOHN SIDNEY STEWART</u> (Type or Print)	X <u>[Signature]</u> (Signature in Full. No initials.)
Citizenship	<u>USA</u>	Date <u>7-30-99</u>
Post Office Address	<u>3655 W. 71st Street, Indianapolis, Indiana 46268</u>	
Residence	<u>Indianapolis (Marion County), Indiana 46268</u>	

609 734 9700